

Selecting the correct REFRIGERATION SYSTEM for your COOLROOM

- STEP 1: Select **STANDARD** or **WITH FLOOR**.
- STEP 2: Select the Room Size column you require. (eg. 1.8 x 1.8m), noting the Room Size model number (eg. M2CR1818)
- STEP 3: Select either **General** or **Heavy** usage.
- STEP 4: Select the type of Motor required (eg. Slide In; Drop In; Split System or Wine Block)
- STEP 5: Reading down the Room size column, find available Motor indicated by green tick ✓

USAGE GUIDELINES	GENERAL USAGE	HEAVY USAGE
	Less than 10 room entries per day Less than 75kg of product per cubic metre Indoor application	10 or more room entries per day (maximum 40 openings) 75kg 0r more of product per cubic metre Indoor application

NB: Usage requires technical knowledge for selecting the correct refrigeration system.

STANDARD								
Room Size (All 2400mm in height)	1.8x1.4m	1.8x1.8m	1.8x2.6m	2.2x2.2m	2.6x2.6m	3.0 x 3.4m		
Coolroom Model No.	M2CR1814	M2CR1818	M2CR1826	M2CR2222	M2CR2626	M2CR3034		
GENERAL USAGE	Drop In Motor							
	MSB125T	✓	✓					
	MSB225N			✓	✓	✓		
	MSB225T						✓	
	Slide In Motor							
	MGM106	✓						
	MGM110		✓					
	MGM211			✓	✓			
	MGM213					✓	✓	
	Split/Remote System Motor							
	MSP121T	✓						
	MSP221N		✓	✓	✓			
	MSP221T					✓	✓	
	Wine Block							
	SLIDE IN	RCV102	✓	✓	✓	✓	✓	
		RCV201						✓
		RCV202	For large rooms and cellars see page 62					
	SPLIT	RDV102	✓	✓	✓	✓	✓	
RDV201							✓	
RDV202		For large rooms and cellars see page 62						
HEAVY USAGE	Drop In Motor							
	MSB225N	✓	✓					
	MSB225T			✓	✓			
	MSB135N					✓		
	MSB135T						✓	
	Slide In Motor							
	MGM211	✓	✓					
	MGM213			✓	✓			
	MGM315					✓		
	MGM320						✓	
	Split/Remote System Motor							
	MSP221N	✓	✓					
MSP221T			✓	✓				
MSP135T					✓	✓		

WITH FLOOR								
Room Size (All 2400mm in height)	1.8x1.4m	1.8x1.8m	1.8x2.6m	2.2x2.2m	2.6x2.6m	3.0 x 3.4m		
Coolroom Model No.	M2CR1814F	M2CR1818F	M2CR1826F	M2CR2222F	M2CR2626F	M2CR3034F		
GENERAL USAGE	Drop In Motor							
	MSB125T	✓	✓	✓	✓			
	MSB225N					✓		
	MSB135N						✓	
	Slide In Motor							
	MGM106	✓	✓					
	MGM110			✓	✓			
	MGM211					✓		
	MGM315						✓	
	Split/Remote System Motor							
	MSP121T	✓	✓					
	MSP221N			✓	✓	✓		
	MSP135T						✓	
	Wine Block							
	SLIDE IN	RCV102	✓	✓	✓	✓	✓	
		RCV201						✓
		RCV202	For large rooms and cellars see page 62					
	SPLIT	RDV102	✓	✓	✓	✓	✓	
RDV201							✓	
RDV202		For large rooms and cellars see page 62						
HEAVY USAGE	Drop In Motor							
	MSB125T	✓						
	MSB225N		✓	✓	✓			
	MSB225T					✓		
	MSB135N						✓	
	Slide In Motor							
	MGM110	✓						
	MGM211		✓	✓	✓			
	MGM213					✓		
	MGM315						✓	
	Split/Remote System Motor							
	MSP221N	✓	✓					
MSP221T			✓	✓	✓			
MSP135T						✓		

Above charts serve as a guide only. Maximum ambient temperature: 45° C. WineBlock: 40° C. See page 56: Pre Installation Checklist.

Installation available in most Metro and major Regional areas subject to:

- Flat and level surface - Clear and easy access installation point (including provision for unloading) - Provision of adequate ventilation and power (within 2m of site) - Additional charges may apply if lifting equipment is required
- Subject to site inspection by a licensed refrigeration technician and completion of Bromic Site Checklist - Call our Sales office to arrange a quotation.

Select the correct REFRIGERATION SYSTEM for your FREEZER ROOM

- STEP 1: Select the Room Size column you require. (eg. 1.8 x 1.8m), noting the Room Size model number (eg. M2FR1818F)
- STEP 2: Select either **General** or **Heavy** usage.
- STEP 3: Select the type of Motor required (eg. Slide In; Drop In; Split System)
- STEP 4: Reading down the Room size column, find available Motor indicated by green tick ✓

USAGE GUIDELINES	GENERAL USAGE	HEAVY USAGE
	Less than 10 room entries per day Less than 75kg of product per cubic metre Indoor application	10 or more room entries per day (maximum 40 openings) 75kg or more of product per cubic metre Indoor application

NB: Usage requires technical knowledge for selecting the correct refrigeration system.

- ✓ Single refrigeration system required
- ✓✓ Two refrigeration systems may be required, depending upon temperature required and ambient temperature. Call Customer Care for assistance

FREEZER ROOM - with floor							
Room Size <small>(All 2400mm in height)</small>	1.8x1.4m	1.8x1.8m	1.8x2.6m	2.2x2.2m	2.6x2.6m	3.0 x 3.4m	
Coolroom Model No.	M2FR1814F	M2FR1818F	M2FR1826F	M2FR2222F	M2FR2626F	M2FR3034F	
GENERAL USAGE	Drop In Motor						
	BSB125T	✓					
	BSB225T		✓	✓	✓		
	BSB135T					✓	✓✓
	Slide In Motor						
	BGM218	✓					
	BGM220		✓	✓	✓		
	BGM320					✓	
	BGM330						✓✓
	Split/Remote System Motor						
	BSP221N	✓	✓				
	BSP135N			✓	✓		
BSP135T					✓	✓✓	
HEAVY USAGE	Drop In Motor						
	BSB225T	✓					
	BSB135T		✓	✓	✓	✓	✓✓
	Slide In Motor						
	BGM320	✓	✓				
	BGM330			✓	✓	✓	✓✓
	Split/Remote System Motor						
	BSP221N						
	BSP135N	✓	✓				
	BSP135T			✓	✓	✓	✓✓

- BSB135T
BSB125T
- BGM330
BGM218
- BSP221N
BSP135T
- BSB135T
BSB125T
- BSB135T
BSB135T
- BGM330
BGM320
- BGM330
BGM218
- BSP135T
BSP135T
- BSP135T
BSP221N

Above charts serve as a guide only. Maximum ambient temperature = 45° C. See page 56: Pre Installation Checklist.

Installation available in most Metro and major Regional areas subject to:

- Flat and level surface - Clear and easy access installation point (including provision for unloading) - Provision of adequate ventilation and power(within 2m of site) - Additional charges may apply if lifting equipment is required
- Subject to site inspection by a licensed refrigeration technician and completion of Bromic Site Checklist - Call our Sales office to arrange a quotation.